

LGMG ELECTRIC MOTOR DRIVE SCISSOR LIFT

SPECIFICATIONS

MODELS	S0808E II (S2632E II)	
Measurements	Metric	Imperial
Work Height Max.	9.8/8m (in/out)	32'2"/26'3" (in/out)
A Platform Height-Raised	7.8/6m (in/out)	25'7"/19'8" (in/out)
B Platform Length	2.26m	7'5"
C Platform Width	0.79m	2'7"
D Overall Length	2.44m	8'
E Overall Width	0.83m	2'9"
F Overall Height-Guardrails Up	2.28m	7'6"
G Overall Height-Guardrails Down	1.9m	6'3"
H Extension Deck	0.9m	2'11"
I Wheelbase	1.85m	6'1"
Ground Clearance(Stowed/Raised)	100/20mm	4"/1"

PRODUCTIVITY

Max. Platform Occupants	2 (in) / 1(out)	
Platform Capacity	230kg	510 lbs
Platform Capacity-Extension Deck	120kg	265 lbs
Drive Height	Full Height	
Gradeability-Stowed	25%	
Min. Turning Radius	2.2m	7'3"
Raise/Lower Speed	31s / 40s	
Brakes	Front-wheel Brake	
Drive Mode	4x2	
Tire Type	Solid Non-marking	
Tire Size	380x130mm	15"x5"

POWER

Power Source	24V 225Ah	
Power Source (S0808EII-Li)	24V 160Ah	

HYDRAULIC SYSTEM

Hydraulic Oil Capacity	13L	3.4gal
------------------------	-----	--------

WEIGHT


Machine Weight(CE/ANSI)	2200kg	4850 lbs
-------------------------	--------	----------

STANDARD FEATURES

Proportional control	Indoor and outdoor rated
Foldable guardrail	Emergency stop device
Manual brake release	Swing-out component tray
Emergency descent	Tilt alarm with lift cut-out
Pothole guard	Overload sensing system
Self-lock entry gate	Descent alarm with flashing beacon
All motions alarm	Intelligent diagnostic system
Full-height drive	Solid non-marking tires

OPTIONAL

AC power to platform	Anti-collision protection
Voice alarm system	Maintenance-free battery
Telematics	Biodegradable hydraulic oil



Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

This brochure comes into effect in May, 2023.

LINGONG HEAVY MACHINERY CO., LTD.

LGMG Europe B.V.

LGMG North America Inc.

LGMG
RELIABILITY IN ACTION